PUMPKIN PRO



■ DescriptionIndoor LED floodlight with professional LEDs and various lens optical systems, making the luminaire suitable for sport halls, warehouses, production areas

Basic information

Family:

Product: **PUMPKIN PRO XXL SH ANT FL IP66 740 447 520x490**

Index: BLS0000014783

Pictograms:












Lighting and electrical parameters


Light source	LED
Luminaire luminous flux [lm]	44795
Power of luminaire [W]	321
Luminaire's light efficiency [lm/W]	140
Color of the light [K]	4000
CRI	>70
Protection against electric shock	1
Protection degree	IP66
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	102000
Lx/By	L90/B10
Operating temperature range [°C]	- 50 ÷ +45
Driver	LED driver

Mechanical parameters:

Assembly	wall-mounted
Material	aluminum
Color	anthracite
Diffuser	SH tempered glass
Impact resistant	IK09
Weight [kg]	6.5
Dimensions [mm]	520 x 490 x 65



A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 17-09-2025



Accessories

Index	BLS0000015166
Name	Złączka IP68 - THB.391.A3A 3P



Index BLS0000015166

Name Złączka IP68 - THB.391.A3A 3P

