

# ORCHID SLIM C PZ



## Description

Surface-mounted luminaire ORCHID SLIM is made out of anodized aluminium profile. ORCHID SLIM luminaire is recommended for: office spaces, schools, universities, conference halls or public administration buildings etc.

## Basic information

|             |                                                   |
|-------------|---------------------------------------------------|
| Family:     | ORCHID SLIM C PZ                                  |
| Product:    | ORCHID SLIM C PZ-1,5m PLX DALI BL 840 29 852 SPAW |
| Index:      | BLS0000014710                                     |
| Pictograms: |                                                   |




## Lighting and electrical parameters

|                                                  |                   |
|--------------------------------------------------|-------------------|
| Light source                                     | LED               |
| <b>Luminaire luminous flux [lm]</b>              | <b>2912</b>       |
| Power of luminaire [W]                           | 26.4              |
| <b>Luminaire's light efficiency [lm/W]</b>       | <b>110</b>        |
| Color of the light [K]                           | 4000              |
| <b>CRI</b>                                       | <b>&gt;80</b>     |
| SDCM (LED sources)                               | 3                 |
| <b>Photobiological risk class (IEC/EN 62471)</b> | <b>RG0</b>        |
| Protection against electric shock                | I                 |
| <b>Protection degree</b>                         | <b>IP44</b>       |
| Voltage                                          | 220-240V, 50-60Hz |
| <b>Lifetime of LED sources [h]</b>               | <b>90000</b>      |
| Lx/By                                            | L70/B10           |
| <b>Operating temperature range [°C]</b>          | <b>5 ÷ 30</b>     |
| Driver                                           | DALI driver       |

## Mechanical parameters:

|                        |                           |
|------------------------|---------------------------|
| Assembly               | pendant - slings required |
| <b>Material</b>        | <b>aluminum</b>           |
| Color                  | black                     |
| <b>Diffuser</b>        | <b>PLX opalized</b>       |
| Impact resistant       | IK06                      |
| <b>Dimensions [mm]</b> | <b>852 x 43 x 61</b>      |



## A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality.

Date of last update: 18-08-2025