




## Description

## Basic information

Family:	<b>NEMESIA IN60</b>
Product:	<b>NEMESIA IN60 SQ BL IP65 840 170x70</b>
Index:	<b>BLS0000015022</b>
Pictograms:	




## Lighting and electrical parameters

Light source	LED
<b>Luminaire luminous flux [lm]</b>	<b>177</b>
Power of luminaire [W]	4
<b>Luminaire's light efficiency [lm/W]</b>	<b>44</b>
Color of the light [K]	4000
<b>CRI</b>	<b>&gt;80</b>
SDCM (LED sources)	5
<b>Protection against electric shock</b>	<b>II</b>
Protection degree	IP65
<b>Voltage</b>	<b>220-240V, 50-60Hz</b>
Lifetime of LED sources [h]	50000
<b>Lx/By</b>	<b>L70/B50</b>
Operating temperature range [°C]	-25 ÷ 30
<b>Driver</b>	<b>LED driver</b>

## Mechanical parameters:

Assembly	wall-mounted
<b>Material</b>	<b>aluminum</b>
Color	black
<b>Diffuser</b>	<b>PC transparent polycarbonate</b>
Impact resistant	IK10
<b>Dimensions [mm]</b>	<b>70 x 70 x 50</b>
Mounting hole [mm]	D60 x 70



## A graph of light