



Description

HOYA luminaire is built from rectangular aluminium profiles that are galvanized. Simple flat shape creates elegantly presenting architectural element. Used LED light sources in this luminaire enables to realize majority of the projects. Application: paths in gardens/parks, entrances to the properties, public spaces.

Basic information

Family:	HOYA LC
Product:	HOYA LC G IP65 ANT 740 ST 57 4000x150x150
Index:	BLS0000016256
Pictograms:	




Lighting and electrical parameters


Light source	LED
Luminaire luminous flux [lm]	5778
Power of luminaire [W]	35
Luminaire's light efficiency [lm/W]	165
Color of the light [K]	4000
CRI	>70
SDCM (LED sources)	3
Protection against electric shock	I
Protection degree	IP65
Voltage	220-240V, 50-60Hz
Lifetime of LED sources [h]	102000
Lx/By	L90/B10
Operating temperature range [°C]	-40 ÷ 50
Driver	LED driver

Mechanical parameters:

Assembly	ground-mounted
Material	aluminum
Color	anthracite
Diffuser	transparent glass lenses
Impact resistant	IK09
Dimensions [mm]	4000 x 150 x 150



A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality.

Date of last update: 18-08-2025

