



# ORCHID SLIM35

## Description

Surface-mounted luminaire ORCHID SLIM is made out of anodized aluminium profile. ORCHID SLIM luminaire is recommended for: office spaces, schools, universities, conference halls or public administration buildings etc.

## Basic information

Family:	<b>ORCHID SLIM35</b>
Product:	<b>ORCHID SLIM35 Z UD PLX/RASTER BL/WH 840 ZAW-1,5m 20/42 1085</b>
Index:	<b>BLS0000016545</b>
Pictograms:	



## Lighting and electrical parameters

Light source	LED
<b>Luminaire luminous flux [lm]</b>	<b>UP - 2315 / DOWN - 4921</b>
Power of luminaire [W]	50.3
<b>Luminaire's light efficiency [lm/W]</b>	<b>124</b>
Color of the light [K]	4000
<b>CRI</b>	<b>&gt;80</b>
SDCM (LED sources)	3
<b>Photobiological risk class (IEC/EN 62471)</b>	<b>RG0</b>
Protection against electric shock	I
<b>Protection degree</b>	<b>IP40</b>
Voltage	220-240V, 50-60Hz
<b>Lifetime of LED sources [h]</b>	<b>90000</b>
Lx/By	L70/B10
<b>Operating temperature range [°C]</b>	<b>5 ÷ 30</b>
Driver	DALI driver

## Mechanical parameters:

Assembly	pendant
<b>Material</b>	<b>aluminum</b>
Color	white
<b>Impact resistant</b>	<b>IK04</b>
Dimensions [mm]	1085 x 35 x 65

## A graph of light

