




ORCHID SLIM35

Description

Surface-mounted luminary ORCHID SLIM is made out of anodized aluminium profile. ORCHID SLIM luminary is recommended for: office spaces, schools, universities, conference halls or public administration buildings etc.

Basic information

Family: **ORCHID SLIM35**
Product: **ORCHID SLIM35 Z PLX WH 840 ZAW-1,5m 46 1135**
Index: **BLS0000016530**
Pictograms:




Lighting and electrical parameters

Light source	LED
Luminaire luminous flux [lm]	4652
Power of luminaire [W]	37.4
Luminaire's light efficiency [lm/W]	124
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP44
Voltage	220-240V, 50-60Hz
Lifetime of LED sources [h]	90000
Lx/By	L70/B10
Operating temperature range [°C]	5 ÷ 30
Driver	DALI driver

Mechanical parameters:

Assembly	pendant
Material	aluminum
Color	white
Diffuser	PLX opalized
Impact resistant	IK04
Dimensions [mm]	1135 x 35 x 65

A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 18-08-2025