




### Description

The PRIMROSE wall luminaire is made of aluminum. The PRIMROSE luminaire is recommended due to its degree of airtightness (IP65), among others for balconies or terraces.

### Basic information

|             |                                    |
|-------------|------------------------------------|
| Family:     | PRIMROSE                           |
| Product:    | PRIMROSE K PLX ANT IP65 840 13 250 |
| Index:      | BLS0000016921                      |
| Pictograms: |                                    |




### Lighting and electrical parameters

|                                            |                            |
|--------------------------------------------|----------------------------|
| Light source                               | LED                        |
| <b>Luminaire luminous flux [lm]</b>        | <b>1361</b>                |
| Power of luminaire [W]                     | 10.6                       |
| <b>Luminaire's light efficiency [lm/W]</b> | <b>128</b>                 |
| Color of the light [K]                     | 4000                       |
| <b>CRI</b>                                 | <b>&gt;80</b>              |
| SDCM (LED sources)                         | 3                          |
| <b>Protection against electric shock</b>   | <b>I</b>                   |
| Protection degree                          | IP65                       |
| <b>Voltage</b>                             | <b>220-240 V, 50-60 Hz</b> |
| Lifetime of LED sources [h]                | 100000                     |
| <b>Lx/By</b>                               | <b>L80/B10</b>             |
| Operating temperature range [°C]           | -30 ÷ +30                  |
| <b>Driver</b>                              | <b>LED driver</b>          |

### Mechanical parameters:

|                    |                     |
|--------------------|---------------------|
| Assembly           | wall-mounted        |
| <b>Material</b>    | <b>aluminum</b>     |
| Color              | anthracite          |
| <b>Diffuser</b>    | <b>PLX opalized</b> |
| Impact resistant   | IK10                |
| <b>Weight [kg]</b> | <b>1.1</b>          |
| Dimensions [mm]    | 250 x 100 x 110     |



### A graph of light

Technical data may be changed. Photos of the luminaires may differ from reality.

Date of last update: 01-08-2025