




Description

The PRIMROSE wall luminaire is made of aluminum. The luminaire has LEDs with a special coating that protects against aggressive factors such as chlorine. The PRIMROSE luminaire is recommended for usage in swimming pools with chlorinated water.

Basic information

Family: PRIMROSE
Product: PRIMROSE K PLX IND ANT IP65 840 13 250
Index: BLS0000016925
Pictograms:




Lighting and electrical parameters

Light source	LED IND
Luminaire luminous flux [lm]	1329
Power of luminaire [W]	10.6
Luminaire's light efficiency [lm/W]	125
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Protection against electric shock	I
Protection degree	IP65
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	-30 ÷ +30
Driver	LED driver

Mechanical parameters:

Assembly	wall-mounted
Material	aluminum
Color	anthracite
Diffuser	PLX opalized
Impact resistant	IK10
Weight [kg]	1.1
Dimensions [mm]	250 x 100 x 110



A graph of light

Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 01-08-2025